

DoP No.: 115-003**1. Unique identification code of the product type:**

Speedline Top Acrylic.

Identification number: See product packaging for the batch number.

2. Intended use:

1-component acrylic sealant. Sealant for use in facades.

3. Name and contact address of distributor:

SIG Benelux
Industrieweg 17, 5145 PD Waalwijk, The Netherlands
(0031) 88 6069 600 | info@sigcs.nl | www.sigbenelux.com

4. Authorized representative:

Not applicable.

5. System for assessing constancy of performance

System 3 plus 3.

6. Harmonized standard

EN 15651 - 1: 2012-12

Notified body: SKZ TeConA GmbH (NB no. 1213) performed the initial testing and the testing and classification as a designated test laboratory in System 3.

7. Declared Performance

Essential characteristic	Performance	Harmonized Technical Specification
Fire Resistance	Class E	EN 15651 - 1: 2012-12 Conditioning: Method A Concrete M2 unprimed Aluminum unprimed
Free from chemicals harmful to health or the environment	NPD	
Sag resistance	≤ 3 mm	
Tensile properties: Elongation at break at 23°C	≥ 100%	
Volume loss	≤ 25%	
Durability	NF	NF = no defects

8. Appropriate technical documentation and/or specific technical documentation

Specific technical documentation: not applicable.

The performance of the product identified in point 1 is in accordance with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Bert de Ru
Managing Director

Date and place:

08-12-2025 | 13:43 CET

Bert de Ru