

Product Name

Speedline Filler 90 HR

Composition

Joint filler for finishing joints with beveled edges in combination with joint tape.

Properties

Powdered joint filler based on gypsum, resin, cellulose fibers, and other aggregates. The prepared paste is white.

Substrate

All types of plasterboard with beveled edges and/or boarded surfaces.

Finish

Speedline Filler 90 HR can be used as a primer for plasterboard and as a gypsum-based finishing plaster.

Mixing Ratio

Add 13 liters of water per 20 kg bag.

Drying Time

The next coat may be applied after the first application has hardened.

Packaging

20 kg in a paper bag.

Storage

Shelf life: approximately 9 months when stored in a cool, frost- and moisture-free, airtight container.



Safety

For safety instructions, consult the Speedline safety data sheet. The information provided is compiled to the best of our knowledge and ability. However, the user must assess the application of this product based on their specific circumstances and capabilities. No liability or warranty can be derived from the text of this technical description.

Disclaimer

The information in this document is intended to inform our customers. It is intended as a guide only and should not be considered a guarantee or quality specification. We are not liable for any (direct or indirect) damage resulting from the use of the product shown in this document. The user is responsible for performing all necessary tests to ensure that the product is suitable for the intended application. We have no influence on the application method of the product or the conditions during storage and transport. We accept no liability for any (typesetting) errors or omissions. This document replaces previous versions.

