

Filler Light

(10, 5, 1 liter en 330 ml)

Product Name

Speedline Filler Light

Composition

Lightweight repair and filler paste for interior use. Speedline Filler Light is a light, white, ready-to-use paste with virtually no shrinkage. Remains flexible and elastic after drying. Applied in a single coat, sand if necessary. Suitable for repairing and filling cracks, holes, and joints.

Technical Properties:

- Density: 0.4.
- pH: 7.
- Shrink-free filling and smoothing.
- Excellent application quality.

Application

Speedline Filler Light is a lightweight repair and filler paste for interior use. Used for repairing and filling cracks, holes, and joints.

Substrate Preparation

The substrate must be free of non-adherent paint, clean, and free of dust.

Substrate

Can be used on various substrates, such as plastered walls, plasterboard, plaster tiles, wooden panels, and aerated concrete. Can also be used to finish perforated plasterboard for seamless (acoustic) ceilings or walls, provided the sides of the boards are impregnated. Do not apply to plastic and/or metal substrates.

Application

Apply Speedline Light with a spatula or putty knife, smoothing after application. For repairs, the paste can be painted over with watercolor paint after 2 hours and with oil-based paint after 24 hours, depending on the thickness.



Packaging

Plastic bucket/tube containing 10, 5, or 1 kg and 330 ml.

Storage

Stored in a cool, frost-free, and airtight container, it has a shelf life of approximately 1 year.

Safety

It is recommended to adequately protect the eyes, nose, mouth, and skin with personal protective equipment during application. Do not inhale dust while sanding. If Speedline Filler Light comes into contact with the eyes, rinse immediately with plenty of clean water (approximately 15 minutes). Consult a doctor afterwards. For more information, see the Speedline safety data sheet.

Specifications

Do not apply below a substrate and air temperature of +5°C or when frost is expected. Adding non-prescribed aggregates is not permitted.

Disclaimer

The information in this document is intended to inform our customers. It is intended as a guide only and should not be considered a guarantee or quality specification. We are not liable for any (direct or indirect) damage resulting from the use of the product shown in this document. The user is responsible for performing all necessary tests to ensure that the product is suitable for the intended application. We have no influence on the application method of the product or the conditions during storage and transport. We accept no liability for any (typesetting) errors or omissions. This document replaces previous versions.

Scan for
product page

