

Product Name

Speedline Flexcorner

Composition

Speedline Flexcorner is a corner protector made of paper tape with two galvanized metal strips. Flexcorner is used to reinforce external corners. The micro-perforations ensure optimal adhesion.

Properties

Very strong paper strength combined with two galvanized metal strips results in an extremely strong corner.

Application

For reinforcing external and internal corners of plasterboard walls.

Technical Data

Total width 52 mm ($\pm 2\%$).

Substrate Pretreatment

Thoroughly remove old, dusty, dirty, and loose layers of plaster and paint. Remove grease and other contaminants.

Substrate

Flexcorner is used to reinforce external corners. Can be used at any angle. The substrate must be load-bearing and stable, free of dust, loose parts, formwork oil, moisture, or other contaminants that could negatively affect adhesion/fastening.

Application

Speedline Flexcorner is used for reinforcing corners. Unroll, fold, and secure on clean, dry, dust- and grease-free seams/surfaces. Can be used from 5°C.



Packaging

Roll width: 52 mm and 30 m.

Storage

Store in a cool, frost-free place in the original packaging, at a temperature of no more than 21°C and a humidity of no more than 50%, and keep away from heat sources and direct sunlight.

Safety

It is recommended that you adequately protect the eyes, nose, mouth, and skin with personal protective equipment when applying pretreatment products.

Special Considerations

Mask the components not to be treated beforehand with paper and adhesive tape. Do not apply below a substrate and air temperature of +5°C or when frost is expected. Tolerance: 5%, unless otherwise stated.

Disclaimer

The information in this document is intended to inform our customers. It is intended as a guide only and should not be considered a guarantee or quality specification. We are not liable for any (direct or indirect) damage resulting from the use of the product shown in this document. The user is responsible for performing all necessary tests to ensure that the product is suitable for the intended application. We have no influence on the application method of the product or the conditions during storage and transport. We accept no liability for any (typesetting) errors or omissions. This document replaces previous versions.

